

# ADDS LittleFoot Terminal Setup

## F1 Options

(Quick)

Emulation: VT200-8  
Comm Mode: Full Duplex  
Enhanced: On  
Host/Printer: EIA/Aux  
EIA Baud Rate: 38400  
Aux Baud Rate: 9600  
Language: US  
EIA Data Format: 8/1/N  
Aux Data Format: 8/1/N  
Sessions: One

## F2 Options

(General)

Emulation: VT200-8  
Auto Font Load: On  
Monitor Mode: Off  
Warning Bell: On  
Sessions: One  
Enhanced: On  
Auto Page: Off  
Screen Saver: 5 minutes  
Bell Length: 350ms  
Color Mode: Direct  
Auto Wrap: Off  
Auto Scroll: On  
Bell Volume: 06  
Host/Printer: EIA/AUX

## F3 Options

(Display)

Page Length: 24  
Display Cursor: On  
Columns: 80  
Scroll: Jump  
Screen Length: 26 Lines  
Cursor: Blink Block  
Width Change Clear: Off  
Erase Color: Background  
Screen Video: Normal  
Auto Adjust Cursor: On  
Speed: Fast

## F4 Options

(Keyboard)

Language: US  
Key Click: Off  
Margin Bell: Off  
Num Lock: Toggle  
Char Set Mode: PC  
Key Repeat: On  
Key Lock: Reverse  
Key Mode: ASCII  
Key Rate: 20cps  
Caps Lock: Toggle

## F5 Options

(Keys)

Enter Key: <CR>  
Alt Key: Compose  
Pound Key: US  
Return Key: <CR>  
Disconnect: Pause  
Return Key Repeat: Off  
Backspace: <BS>/<DEL>  
Desk Acc: Disabled  
UDKs: Emul Dependent

## F6 Options

(Ports)

EIA Baud Rate: 38400  
Aux Baud Rate: 9600  
EIA Xmt: Xon-Xoff  
Aux Xmt: Xon-Xoff  
EIA Break: 250ms  
Aux Break: 250ms  
EIA Data Format: 8/1/N  
Aux Data Format: 8/2/N  
EIA Rcv: Xany-Xoff(XPC)  
Aux Rcv: Xon-Xoff(XPC)  
EIA Modem Control: Off  
Aux Modem Control: Off  
EIA Parity Check: Off  
Aux Parity Check: Off  
EIA Xmit Pace: Baud  
Aux Xmit Pace: Baud  
EIA Disconnect: 2sec  
Aux Disconnect: 2sec

## F7 Options

(Host)

Comm Mode: Full Duplex  
Recv<DEL>:Ignore  
Send Region: Screen  
Alt Input Data: On  
Local: Off  
Send ACK: On  
Send END: Region  
Rec<CR>: <CR>  
Send Block Term: None  
Num Suppress: Off

## F8 Options

(Print)

Print Mode: Auto  
Secondary Recv: On  
Print Region: Screen  
Print Block Term: None

## F9 Options

(Emul)

Numeric KPD: Numeric  
Print: National  
Feature Lock: Off  
Cursor KPD: Cursor  
ANSI-ID: VT220  
Status Line: Indicator  
Send Data: All  
Function Key Lock: Off